

(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 606 131 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
02.01.2003 Bulletin 2003/01

(51) Int Cl.7: **H04N 1/32**

(21) Application number: **94300006.7**

(22) Date of filing: **04.01.1994**

(54) Method for compiling multiple jobs with job reference sheets

Verfahren zum Zusammenfügen vielfältiger Aufgaben mit Aufgabenbezugsblättern

Méthode pour la compilation de travaux multiples avec les feuilles de travail de référence

(84) Designated Contracting States:
DE FR GB

(30) Priority: **04.01.1993 US 165**

(43) Date of publication of application:
13.07.1994 Bulletin 1994/28

(73) Proprietor: **XEROX CORPORATION**
Rochester, New York 14644 (US)

(72) Inventor: **Hube, Randall R.**
Rochester, New York 14625 (US)

(74) Representative: **Grünecker, Kinkeldey,**
Stockmair & Schwanhäusser Anwaltssozietät
Maximilianstrasse 58
80538 München (DE)

(56) References cited:
EP-A- 0 366 425 **EP-A- 0 478 270**
US-A- 4 987 447

EP 0 606 131 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] The present invention relates generally to a technique for an electronic printing system, and, more specifically, to a method for compiling a plurality of jobs into an assembled job.

[0002] High speed electronic copying and printing machines convert original images into image signals or pixels, and in that form process the image signals to provide the desired output which typically is in the form of copies or prints. Machines of this type naturally are and indeed expected to be highly automated to speed up job production and reduce operator time and involvement to the barest minimum.

[0003] Because of their high capacity, speed, and versatility, these machines are particularly suitable for use in central facilities or sites such as commercial printing establishments, in-plant copying and printing departments, etc. These applications typically queue jobs through all stages of the work process and utilize tools such as 'job tickets' to direct the work flow. These 'tickets' provide the direction to operators of the equipment to act on the hard documents being readied for production, the instructions serving as programming parameters to transform the original documents (galleys/graphics/pictures, etc.) from separate entities into integrated structures that are then ready for printing onto various types of substrates.

[0004] To allow the operator to efficiently manage jobs by performing tasks in efficient clumps, it is desirable to program ahead several jobs at once. That is, the operator/shop will seek to queue operations so that incoming jobs will be stacked prior to programming following which the individual stacks are programmed. Once the jobs are programmed, the operator can then place the job in the input hopper for processing.

[0005] The following patents relate to electronic printing systems employing job and/or page separators to control the printing of a job:

US-A-4,716,438
 Patentee: Farrell
 Issued: December 29, 1987
 US-A-4,757,348
 Patentees: Rourke et al.
 Issued July 12, 1988
 US-A-4,970,554
 Patentee: Rourke
 Issued: November 13, 1990
 US-A-4,987,447
 Patentee: Ojha
 Issued: January 22, 1991

[0006] Each of the above-indicated patents discloses the use of job and page separators to program a high speed printing machine in which the separators, which are designed to be added to and scanned with the document originals being processed, bear job programming

information in the form of a bar code. The job and page separators are scanned by the machine document scanner, distinguished from the document originals and the bar code read to provide control instructions for operating the printing machine. Additionally, each of the above-indicated patents, discloses that the separators can be generated by the printing machine or a suitable off-site device capable of generating bar codes compatible with the printing machine.

[0007] While each of the above-discussed separators serves as a pointer to indicate where a suitable set of Job Programming instructions resides in the printing machine, none of those separators indicates how one job can be combined with another job. For example, in certain printing systems, such as the printing system disclosed by US-A-4,970,554, a plurality of jobs can be stored in a printing system for subsequent printing, and yet the respective separators are not adapted to indicate the location of that job. Accordingly, these separators cannot be employed to combine the plurality of jobs into a single master job.

[0008] In the electronic printing system known as DocuTech™, manufactured by Xerox® Corporation, various parts of a job can be merged through use of a job supplement mode, the details of which are discussed in US-A-5,081,494

[0009] In practice, the job supplement is used to supplement a job as it is being scanned into the printing system. That is, when the job supplement mode is engaged, any number of additional documents or groups of documents may be scanned in with the job being scanned. Upon supplementing the job at the scanner, an END JOB icon is selected, and the supplemented job is stored in a memory section of the printing system.

[0010] A current approach for assembling a plurality of jobs on the DocuTech™ printing system to form a single job comprises the following steps:

- 1) Wait for all of the jobs to arrive at a holding repository;
- 2) Establish a "master" document by either choosing one of the jobs as a "master component" or creating a new "blank" master document;
- 3) Open (or edit) the master document;
- 4) Copy the other remaining jobs into the master document, one-by-one, by selecting the page location where each job is to be inserted. During this step, the operator must take care to understand that page numbers after the insertion point gets changed each time a job is inserted;
- 5) Close the master document and develop job level instructions for the master document (such as instructions relating to binding, stitching, copy count, etc.); and
- 6) Copy the master document to a printer queue for proofing or final printing.

[0011] For a printing system which "decomposes" a

stream of image data written in a page description language ("PDL"); the following reference suggests an approach for merging a plurality of jobs through use of the PDL

Harrington, S. J. and Buckley, R. R.
Interpress: The Source Book
pp. 371-379
Simon & Schuster, Inc.
New York, N. Y.
1988

[0012] The above reference discloses an example in which a program, written in a PDL, "namely Interpress", is employed to combine a plurality of masters into a single master. The resulting master is relatively small because it includes references only to component files and not to their contents. Furthermore, if a component is revised, the overall document automatically contains the revision. There is no danger of inconsistency between the components and the combined masters.

[0013] With the current approach for assembling a plurality of jobs on the DocuTech™ printing system, assembling the master job can be time-consuming and tedious, particularly when the above-mentioned step 4) must be repeated numerous times. Additionally, while the technique taught by "The Source Book" appears to be quite eloquent, the technique is intended for use on a printing system that uses a PDL. It would be desirable to provide a technique for compiling a plurality of jobs into a single, assembled job in an efficient manner which does not require any programming with a PDL as not all systems support PDL input.

[0014] Accordingly, it is the object of the present invention to provide a method and an electronic printing system that facilitates the assembly of print jobs.

[0015] This object is solved by the method according to claim 1 and by the electronic printing system according to claim 4. Preferred embodiments are the subject-matter of the dependent claims.

[0016] The present invention will be described further, by way of a preferred embodiment, with reference to the accompanying drawings, in which:-

Figure 1 is a perspective, schematic view of an electronic printing system upon which a preferred job assembling technique can be used.

Figure 2 is a block diagram depicting the major elements of the printing system shown in Figure 1; Figures 3-5 comprise a block diagram showing the major parts of the control section for the printing system shown in Figures 1 and 2,

Figure 6 is a view depicting an exemplary job programming ticket and job scorecard displayed on a User Interface (UI) of the printing system shown in Figure 1, the job ticket and job scorecard being associated with a job to be primed;

Figure 7 is a view of a user interface touchscreen

display depicting a job queue or job file, the job file containing jobs stored in memory of the printing system;

Figure 8 is a perspective, exploded view of a stack of documents arranged for scanning with the stack being segregated into a set of originals inserted between a plurality of job reference sheets;

Figures 9A and 9B are flow diagrams which serve conjunctively to illustrate a preferred approach for creating one of the job reference sheets of Figure 8; Figure 10 is a view of the user interface touchscreen display illustrating the manner in which a specific job in the job file is accessed for printing a job reference sheet;

Figures 11 and 12 are flow diagrams which serve conjunctively to illustrate the manner in which a stack, including one or more documents, is compiled into an assembled job

[0017] Referring to the drawings where like reference numerals designate identical or corresponding parts throughout the several views, and more particularly to Figures 1 and 2, there is shown an exemplary image printing system 2 for processing print jobs in accordance with the teachings of the present invention. Printing system 2, for purposes of explanation, is divided into image input section 4, controller section 7, and printer section 8. In the example shown, the image input section 4 has both remote and on-site image inputs, enabling system 2 to provide network, scan, and print services. Other system combinations may be envisioned such as a stand alone printing system with on-site image input (i. e., a scanner), controller, and printer; a network printing system with remote input, controller, and printer; etc.

[0018] While a specific printing system is shown and described, the present invention may be used with other types of printing systems. For example, printer section 8 may instead use a different printer type such as ink jet, ionographic, thermal, photographic, etc., and, furthermore, may be incorporated in electronic display systems, such as CRTs, LCDs, LEDs, etc. or else other image scanning/processing/recording systems, or else other signal transmitting/receiving, recording systems, etc. as well.

[0019] For off-site image input, image input section 4 has a network 5 with a suitable communication channel such as a telephone line enabling image data in the form of image signals or pixels from one or more remote sources to be input to system 2 for processing. Other remote sources of image data such as streaming tape, floppy disk, video camera, etc. may be envisioned.

[0020] For on-site image input, section 4 has a document scanner section 6 with a Universal Document Handler (UDH) 35 for the purpose of automatically and sequentially placing and locating sets of multiple documents for scanning. Scanner section 6 incorporates one or more linear light sensitive arrays 24 for reciprocating scanning movement below platen 20 and focused on a

line-like segment of platen 20 and the document being scanned thereon. Array 24, which may utilize Charge-Coupled Device (CCD) technology or the like, provides image elemental signals or pixels representative of the image scanned which are input to processor 25 for processing.

[0021] Processor 25 communicates with the controller section 7 and includes a scanner system control 25a, an automatic gain control printing wiring board (AGCPWB) 25b, and a processor 25c. AGCPWB 25b converts the analog image signals output by array 24 to digitally represented facsimile signals and processor 25c processes the digital image signals as required to enable controller section 7 to store and handle the image in the form and order required to carry out the job programmed. After processing, the image signals are output to controller section 7. Image signals derived from net 5 are similarly input to processor 25c.

[0022] Processor 25c also provides enhancements and changes to the image signals such as filtering, thresholding, screening, cropping, scaling (reduction/enlargement), etc. Following any changes and adjustments in the job program which affect these image processing parameters, the document must be rescanned to capture the specified modification.

[0023] Printer section 8 comprises a laser type printer having a Raster Output Scanner (ROS) 87, Print Module 95, Paper Supply 107, Finisher 120, and Printer System Control 128. ROS 87 has a two beam laser with the beams modulated in accordance with the content of an image signal input by acousto-optic modulator to provide dual imaging beams which are scanned across a moving photoreceptor of Print Module 95 by means of a rotating polygon. This exposes two image lines on the photoreceptor with each scan to create the latent electrostatic images represented by the image signal input to the modulator.

[0024] The latent electrostatic images are developed and transferred to a print media delivered by paper supply 107. As will be appreciated by those skilled in the art, print media can comprise a selected one of various known substrates which are capable of accepting an image, such substrates including transparencies, preprinted sheets, vellum, glossy covered stock, film or the like. The print media may comprise any of a variety of sheet sizes, types, and colors, and for this, plural media supply trays 110, 112, 114 (Figure 1) are provided. The transferred image is permanently fixed or fused and the resulting prints discharged to either output tray 118 (Figure 1), or to finisher 120. Finisher 120 provides certain finishing selections such as a stitcher for stitching or stapling the prints together to form books, a thermal binder for adhesively binding the prints into books, and/or other finishing options such as slitting, perforating, saddle stitching, folding, trimming, or the like.

[0025] Printer system control 128 (Figure 2) automatically and precisely controls all the printer functions and operations in accordance with job program parameters

received from system control 54 of controller section 7, as well as from internally derived signals from sensors and processes within the printer section 8. Printer system control signals are derived and distributed via a plurality of printed wiring boards (PWBs) in a multi-processor architecture characterized by multiple microprocessor controller cores, serially interconnected, and also serially linked to more numerous input/output processing circuit PWBs. Controller section 7 is, for explanation purposes, divided into an image input control 50, User Interface (UI) 52, system control 54, main memory 56, image manipulation section 58, and image output control 60. The units 50, 54, 56, 58, 60 comprise a system which may also generally be referred to as the "Electronic Subsystem" (ESS).

[0026] The scanned image data input from processor 25c of scanner section 6 to controller section 7 is compressed by image compressor/processor 51 of image input control 50 and placed in an image file. Image files, which represent different print jobs, are temporarily stored in system memory 61 (seen in Figure 3) pending transfer to main memory 56 where the data is held pending use.

[0027] Referring again to Figure 1, UI 52 includes a combined operator controller/CRT display consisting of an interactive touchscreen 62, keyboard 64, and mouse 66. UI 52 interfaces the operator with printing system 2, enabling the operator to program print jobs and other instructions, and to obtain system operating information, visual document facsimile display, programming information and icons, diagnostic information and pictorial views, etc. Items displayed on touchscreen 62 such as files and icons are actuated by either touching the displayed item on screen 62 with a finger, or by using mouse 66 to point cursor 67 (Figure 4) to the item selected and keying the mouse.

[0028] Main memory 56 (Figure 2) has plural hard disks 90-1, 90-2, 90-3 for storing machine Operating System software, machine operating data, and the scanned image data currently being processed. When the compressed image data in main memory 56 requires further processing, is required for display on touchscreen 62 of UI 52 or is required by printer section 8, the data is accessed in main memory 56. Where further processing other than that provided by processor 25 is required, the data is transferred to image manipulation section 58 where the additional processing steps such as collation, make ready (document editing), decomposition, rotation, etc., are carried out. Following processing, the data may be returned to main memory 56, sent to UI 52 for display on touchscreen 62, or sent to image output control 60.

[0029] Referring particularly to Figures 3-5, image data output to image output control 60 is decompressed and readied for printing by image generating processors 86 of printed wiring boards ("PWBs") 70-7, 70-8. Following this, the data is output by dispatch processors 88, 89 on PWB 70-9 via Scan Line Buffer (SLB) 139 (Figure

2) to printer section 8. Image data sent to printer section 8 for printing is normally purged from memory 56 to make room for new image data.

[0030] Control section 7 includes a plurality of PWBs 70 (Figures 3-5), PWBs 70 being coupled with one another and with System Memory 61 by a pair of buses 72, 74. In the preferred embodiment, the System Memory includes a suitable programs for assigning unique job identifiers to each of the jobs inputted to or associated with the printing system 2 and for generating a printable representation, such as an encoded rasterized bar code, for each job. A memory controller 76 couples System Memory 61 with buses 72, 74. PWBs 70 include system processor PWB 70-1 having plural system processors 78; low speed I/O processor PWB 70-2 having UI communication controller 80 for transmitting data to and from UI 52; PWBs 70-3, 70-4, 70-5 having disk drive controller/processor 82 for transmitting data to and from disks 90-1, 90-2, 90-3 respectively of main memory 56 (image compressor/processor 51 for compressing the image data is on PWB 70-3); image manipulation PWB 70-6 with image manipulation processors of image manipulation section 58; image generation processor PWBs 70-7, 70-8 with image generation processors 86 for processing the image data for printing by printer section 8; dispatch processor PWB 70-9 having dispatch processors 88, 89 for controlling transmission of data to and from printer section 8; and boot control-arbitration-scheduler PWB 70-10.

[0031] Referring to Figure 6, jobs are programmed in a Job Program mode in which there is displayed on touchscreen 62 a Job Ticket 150 and a Job Scorecard 152 for the job being programmed. Job Ticket 150 displays various job selections available for programming, while Job Scorecard 152 displays the basic instructions to the system for printing the job. Various Job Ticket types are provided, with access by means of Job Types and Tickets icon 157.

[0032] Each Job Ticket 150 has two programming levels, referred to as "Job Level" and "Page Level", each having a series of icons for accessing the various programming selections available at that level. In the illustrated embodiment of Figure 6, the page level instructions are set off in two sublevels, namely "Basic" and "Special" instructions. Each programming level has a Scorecard 152 associated with it so that on activation of a particular job level or of a specific icon, the appropriate Scorecard is displayed on touchscreen 62.

[0033] As described, print jobs may be derived from multiple sources, i.e., jobs scanned in using scanner 6 for printing; jobs scanned in, stored, and then edited or added to for printing later; jobs remotely scanned in and submitted to the system as, for example, through net 5 (Figure 2); jobs remotely developed and then submitted to the system for printing, etc.

[0034] Referring to Figure 7, the image files are arranged in a job file 155, with the print jobs 156 numbered consecutively in the order in which the print jobs are

scanned in. Where the operator wishes to see the jobs currently residing in job file 155, a JOB FILE icon 157 on touchscreen 62 is actuated. This displays a list of the jobs 156 currently in the job file on screen 62, an example of which is shown in Figure 9. Each job is identified by a descriptor showing the type of job, job number, number of prints, etc. By using up and down scrolling icons 161, 162, the operator can scroll the list of jobs where the number of jobs in the job file is too large to be simultaneously displayed on touchscreen 62.

[0035] Referring to Figure 8, an exemplary approach for compiling a plurality of jobs is shown. The exemplary approach includes the step of physically assembling a job with various components, namely 1-to-n job reference sheets 170 and 0-to-m sets 172 of hard-copy originals, and scanning the various components. In practice, various components are arranged in an ordered stack 173, the order of the stack corresponding to the order in which a master document, i. e. a compilation of various jobs, is to be printed. The ordered components are inputted to the system with the scanner section 6.

[0036] Referring to Figures 9A and 9B, an exemplary procedure for developing and printing each of the job reference sheets 170 is shown. Referring specifically to Figure 9A, at step 174, a network or hard-copy job is received with its Job Programming instructions, the instructions being inputted via the job ticket 150 (Figure 6) or via an electronic equivalent that is received via the network 5 (Figure 2) and having both job level and page level instructions. For a hard-copy job, the scanner section 6 is used to input the image data to be represented by the job reference sheet 170, while, for a network job, image data can be received by way of the network 5 (Figure 2), or may be retained in a remote storage section, referenced by pointer from the printing system 2 and retrieved when actually needed.

[0037] Preferably, each job is programmed with at least two job level designators, namely a job name and job disposition. Upon receiving the job, from either the scanner or the remote storage source, the job is assigned a unique identifier (step 176) with the assigning program of the system memory 61. As further illustrated by step 176, a unique job identifier can be assigned to one or more portions of the job, rather than the entire job itself, without altering the concept upon which the present invention is based. As can be appreciated by those skilled in the art, the capability to print portions of a stored job facilitates the process of "demand publication" As can further be appreciated by those skilled in the art, the assigning program typically would include a database for facilitating the process of assigning the unique job identifiers and for storing the identifiers. The database could be constructed readily by reference to one of several known texts, such as the following text:

Martin, J.
Computer Data-Base Organization
Prentice Hall, Inc.

Englewood Cliffs, New Jersey
1975

[0038] After a unique job identifier is assigned to a given job, the job is stored in the job file 155 of Figure 7 (step 178) or, alternatively, in the remote storage section. While, preferably, the identifiers are stored in the above-mentioned database of system memory 61, they could, alternatively, be stored along with their respective jobs.

[0039] Referring conjunctively to Figures 9B and 10, at step 182, the user "selects" the job in the job file 155 and, at step 184, specifies the number of job reference sheets to be printed. Upon selecting one of the jobs 156, with either a fingertip or the point cursor 67, the selection menu 190 is actuated. For ease of discussion, the highlighted job is designated with the numeral 156'. At step 186 the database of system memory 61 is accessed for retrieving a unique job identifier from the system memory 61, the identifier corresponding to the job 156'. The retrieved identifier is then encoded into a rasterized bar code, at step 188, with any conventional technique, such as the technique referred to as "Matrix 2 of 5". It will be appreciated that the identifier could be translated into various other codes, such as "glyphs", "mark-sense", etc. To print the job reference sheet corresponding to job 156' (step 191), the area indicated as "PRINT JOB REFERENCE SHEET" is actuated with the fingertip or point cursor. As suggested by US-A-5,164,842 to Gauronski et al., the software associated with the selection menu 190 can be modified readily for printing a plurality of copies from a given job reference sheet.

[0040] Referring again to Figure 8, a job title, along with copies of a bar code, are printed on each job reference sheet in a manner consistent with the disclosure of US-A-4,757,348 to Rourke et al. As can be recognized, for each job reference sheet, copies of a single bar code are distributed about the sheet so that proper scanning of the sheet is insured.

[0041] Referring to Figures 11 and 12, a preferred technique for processing any assembled combination of job reference sheets 170 and sets 172 is discussed in further detail. To begin the assembling technique (step 200), the user arranges (per step 202) one or more appropriate job reference sheets 170, and any additional sets of originals 172 into a desired order to form a stack. As will appear the order in which the sheets 170 and sets 172 are arranged determines the order in which the assembled job is compiled. Once the stack is loaded into the UDH 35 (Figure 2) (step 204) and the Job Programming Instructions for the assembled job are programmed (step 206), the scanner/UDH is started so that that each page of the stack is scanned.

[0042] A variable "CURRENT PAGE" is initialized at step 209 and thereafter used to maintain a count throughout a job compiling process. As a page is scanned (step 210), the corresponding page image is analyzed (step 212) for the presence of a job reference

bar code. If a job reference bar code is found, then the process proceeds to step 218 (Figure 12) where the bar code is decoded into a corresponding unique job identifier. Pursuant to the decoding step, a job referenced by the identifier is located in memory of the printing system and opened (step 220). It should be recognized that the location referenced by the identifier could comprise a pointer to a remote storage section linked to the printing system by the Net 5 (Figure 2).

[0043] A variable "REFERENCE PAGE" is initialized at step 222 and thereafter used to maintain a count throughout a process of retrieving the referenced job. In the loop defined by steps 224, 226, 228 and 230, copies of the pages in the referenced job are retrieved (step 224) and inserted into a memory section referred to as "Assembled Job", at the memory location of CURRENT PAGE (step 226). It will be appreciated by those skilled in the art that, in another embodiment, the pages for the reference job could be referenced in the memory section of Assembled Job with a referencing scheme so that retrieving of copies would not be required. To maintain the count of the Assembled Job, the variable CURRENT PAGE is incremented (step 228), and to keep track of the number of pages which have been retrieved from the referenced job, the variable REFERENCE PAGE is incremented (step 230).

[0044] When it is determined that each page of the referenced job has been copied to Assembled Job (step 232), then the referenced job is closed (step 234) and the process returns to step 240 for determining whether any more pages in the stack need scanning. Referring again to step 214 of Figure 11, each page of the stack which is not coded is stored in the Assembled Job (step 236) at the location of CURRENT PAGE. Accordingly, the value of CURRENT PAGE is incremented (step 238) each time a page is stored and the process moves on to step 240. If more pages exist in the stack being scanned, then the process loops to step 210 until each page has been scanned appropriately. If, on the other hand, all of the pages in the stack have been scanned, then Assembled Job is closed and made available for printing.

[0045] The following example will serve to demonstrate how the above-described process facilitates demand publication. Referring again to Figure 8, the various components of the stack are referred to as "A", "B", "C", "D" and "E". Moreover the job is subject to the following constraints: First, each of the components is provided to the print system operator ("operator") at a different moment in time. Indeed, component D is not made available until months after the delivery of component A. Second, it is, due to customer demand, necessary to break the set D into four portions, namely "D1", "D2", "D3" and "D4". Third, customer demand dictates the following printing requirements:

- 1) 10000 copies of "AC(D1)E";
- 2) 10000 copies of "AB(D2)E";

- 3) 10000 copies of "ABC(D3)"; and
- 4) 10000 copies of "BC(D4)E"

Finally, due to the size of the job, the operator cannot print all of the copies at one time.

[0046] In accordance with the above-described technique, jobs A, B, C and E are scanned in, as they become available, and three sets of job reference sheets ABCE are printed and stored for later use. When all of the components are available for D, it is portioned into D1, D2, D3 and D4, and arranged with the job reference sheets to form four stacks, corresponding to the above printing requirements. For each stack, a suitable set of Job Programming Instructions is inputted with the UI 52 (Figure 2) and the stack is then scanned for creating an Assembled Job in memory of the print system 2. With the four Assembled Jobs stored in memory, the operator prints the required copies for the Assembled Jobs as available time arises.

[0047] In view of the above description, numerous features of the disclosed embodiment will be recognized by those skilled in the art. One feature of the disclosed embodiment is to facilitate demand publication. As demonstrated by the example above, the disclosed assembling technique provides the customer(s) and print system operator with a high degree of flexibility. For example, the customer can customize publication by either adding certain components to or omitting certain components from a given stack. Another feature of the disclosed embodiment is to simplify the process of arranging, and ultimately printing, a multi-job document. For example, arranging a stack with hard-copy documents permits the print system operator to locate the insertion points for various components with great ease. Yet another feature of the disclosed embodiment is to save time for the print system operator by eliminating the need to perform extensive open and copy operations in developing an Assembled Job. Yet another feature of the disclosed embodiment is to maximize the productivity for certain types of jobs. For example, the disclosed assembling technique facilitates the printing of complex jobs that have been "proofed" and are now ready for final printing.

Claims

1. A method of forming an assembled job from a first job (156), represented by a first set of electronic pages, and a second job (156), represented by a second set of electronic pages, in an electronic printing system (2) having a printer (8) and a scanner (6) adapted to convert the jobs (156) into sets of electronic pages and to decode machine-readable code, comprising the steps of:

scanning said first and second job to generate said first and second sets of electronic pages,

storing the first set of electronic pages at a first location in a memory section (61);
assigning a first unique job identifier to the stored first job (156) for indicating the first location of the stored first job (156) in the memory section (61);

on demand, automatically printing a first job reference sheet (170) comprising the first unique job identifier in machine-readable code;
storing the second set of electronic pages at a second location in the memory section (61);
assigning a second unique job identifier to the stored second job (156) for indicating the second location of the stored second job (156) in the memory section (61);
on demand, automatically printing a second job reference sheet (170) comprising the second unique job identifier in machine-readable code;
upon scanning the first job reference sheet (170):

reading the first unique job identifier comprised on the first job reference sheet (170), and
accessing the first set of electronic pages stored at the first location in the memory section (61) identified by the read first unique job identifier (170);

upon scanning the second job reference sheet (170):

reading the second unique job identifier comprised on the second job reference sheet (170), and
accessing the second set of electronic pages stored at the second location in the memory section (61) identified by the read second unique job identifier;

in response to the scanning the first job reference sheet (170) and the second job reference sheet (170):

compiling the first set of electronic pages with the second set of electronic pages, and storing said compiled set at a memory location to form the assembled job.

2. The method as claimed in claim 1, further comprising the step of: printing the assembled job with the printer (8).
3. The method as claimed in claim 1 or 2, wherein the scanning steps further comprise the step of:

analyzing a scanned job reference sheet (170) and each scanned original for determining

whether machine-readable code is present.

4. An electronic printing system (2) for forming an assembled job from a first job (156), represented by a first set of electronic pages, and a second job (156), represented by a second set of electronic pages, comprising:

a scanner (6) being adapted to convert the first job (156) into the first set of electronic pages and the second job (156) into the second set of electronic pages;

means (61) for storing the first set of electronic pages at first location and the second set of electronic pages at second location;

means being adapted to assign a first unique job identifier to the stored first job (156) for indicating the first location of the stored first job (156) and a second unique job identifier to the stored second job (156) for indicating the second location of the stored second job (156);

a printer (8) being adapted to print on demand automatically a first job reference sheet (170) comprising the first unique job identifier in machine-readable code and a second job reference sheet (170) comprising the second unique job identifier in machine-readable code;

the scanner (6) further being adapted to scan the first job reference sheet (170) and the second job reference sheet (170), and to decode machine-readable code, for reading the first unique job identifier comprised on the first job reference sheet (170) and reading the second unique job identifier comprised on the second scanned job reference sheet (170);

means for accessing the first set of electronic pages stored at the first location identified by the read first unique job identifier and the second set of electronic pages stored at the second location identified by the read second unique job identifier; and

means adapted to compile, in response to scanning the first job reference sheet (170) and the second job reference sheet (170), the first set of electronic pages with the second set of electronic pages and to store said compiled set at a memory location to form the assembled job."

5. The electronic printing system (2) as claimed in claim 4, further comprising:

means for analyzing the scanned job reference sheet (170) and each scanned original for determining whether machine-readable code is present.

Patentansprüche

1. Verfahren zum Bilden eines zusammengestellten Auftrags von einem ersten Auftrag (156), dargestellt durch einen ersten Satz von elektronischen Seiten, und einem zweiten Auftrag (156), dargestellt durch einen zweiten Satz von elektronischen Seiten, in einem elektronischen Drucksystem (2), das einen Drucker (8) und eine Abtasteinrichtung (6) besitzt, angepasst so, um die Aufträge (156) in Sätze von elektronischen Seiten umzuwandeln und um einen maschinen-lesbaren Code zu decodieren, aufweisend die Schritte:

Abtasten des ersten und des zweiten Auftrags, um den ersten und den zweiten Satz von elektronischen Seiten zu erzeugen,

Speichern des ersten Satzes von elektronischen Seiten an einer ersten Stelle in einem Speicherabschnitt (61);

Zuordnen eines ersten, eindeutigen Auftrag-Identifizierers zu dem gespeicherten, ersten Auftrag (156) zum Anzeigen der ersten Stelle des gespeicherten, ersten Auftrags (156) in dem Speicherabschnitt (61);

auf Anforderung, automatisches Drucken eines ersten Auftrag-Referenz-Blatts (170), das den ersten, eindeutigen Auftrag-Identifizierer in einem maschinen-lesbaren Code aufweist;

Speichern des zweiten Satzes von elektronischen Seiten an einer zweiten Stelle in dem Speicherabschnitt 61;

Zuordnen eines zweiten, eindeutigen Auftrag-Identifizierers zu dem gespeicherten, zweiten Auftrag (156) zum Anzeigen der zweiten Stelle des gespeicherten, zweiten Auftrags (156) in dem Speicherabschnitt (61);

auf Anforderung, automatisches Drucken eines zweiten Auftrag-Referenz-Blatts (170), das den zweiten, eindeutigen Auftrag-Identifizierer aufweist, in einem maschinen-lesbaren Code;

unter Abtasten des ersten Auftrag-Referenz-Blatts (170):

Lesen des ersten, eindeutigen Auftrag-Identifizierers, vorhanden auf dem ersten Auftrag-Referenz-Blatt (170), und

Zugreifen auf den ersten Satz von elektronischen Seiten, gespeichert an der ersten Stelle in dem Speicherabschnitt (61), identifiziert durch den gelesenen, ersten, eindeutigen Auftrag-Identifizierer (170);

Unter Abtasten des zweiten Auftrag-Referenz-Blatts (170):

Lesen des zweiten, eindeutigen Auftrag-Identifizierers, vorhanden auf dem zweiten Auftrag-Referenz-Blatt

- (170), und
 Zugreifen auf den zweiten Satz von elektronischen Seiten, gespeichert an der zweiten Stelle in dem Speicherabschnitt (61), identifiziert durch den gelesenen, zweiten, eindeutigen Auftrag-Identifizierer;
 auf das Abtasten des ersten Auftrag-Referenz-Blatts (170) und des zweiten Auftrag-Referenz-Blatts (170) hin:
 Zusammenstellen des ersten Satzes von elektronischen Seiten mit dem zweiten Satz von elektronischen Seiten, und Speichern des zusammengestellten Satzes an einer Speicherstelle, um den zusammengestellten Auftrag zu bilden.
2. Verfahren nach Anspruch 1, das weiterhin den Schritt eines Druckens des zusammengestellten Auftrags mit dem Drucker (8) aufweist.
3. Verfahren nach Anspruch 1 oder 2, wobei die Abtastschritte weiterhin den Schritt aufweisen:
- Analysieren eines abgetasteten Auftrag-Referenz-Blatts (170) und jedes abgetasteten Originals zum Bestimmen, ob ein maschinen-lesbarer Code vorhanden ist.
4. Elektronisches Drucksystem (2) zum Bilden eines zusammengestellten Auftrags von einem ersten Auftrag (156), dargestellt durch einen ersten Satz von elektronischen Seiten, und einem zweiten Auftrag (156), dargestellt durch einen zweiten Satz von elektronischen Seiten, aufweisend: eine Abtasteinrichtung (6), die so angepasst ist, um den ersten Auftrag (156) in den ersten Satz von elektronischen Seiten und den zweiten Auftrag (156) in den zweiten Satz von elektronischen Seiten umzuwandeln; eine Einrichtung (61) zum Speichern des ersten Satzes von elektronischen Seiten an einer ersten Stelle und des zweiten Satzes von elektronischen Seiten an einer zweiten Stelle; eine Einrichtung, die so angepasst ist, um einen ersten, eindeutigen Auftrag-Identifizierer dem gespeicherten, ersten Auftrag (156) zum Anzeigen der ersten Stelle des gespeicherten, ersten Auftrags (156) und einen zweiten, eindeutigen Auftrag-Identifizierer zu dem gespeicherten, zweiten Auftrag (156), um die zweite Stelle des gespeicherten, zweiten Auftrags (156) zum Anzeigen, zuzuordnen; einen Drucker (8), der so angepasst ist, um auf Anforderung automatisch ein erstes Auftrag-Referenz-Blatt (170), das den ersten, eindeutigen Auftrag-Identifizierer in einem maschinen-lesbaren Code aufweist, und ein zweites Auftrag-Referenz-Blatt (170), das den zweiten, eindeutigen Auftrag-

Identifizierer in einem maschinen-lesbaren Code aufweist, zu drucken;
 wobei die Abtasteinrichtung (6) weiterhin so angepasst ist, um das erste Auftrag-Referenz-Blatt (170) und das zweite Auftrag-Referenz-Blatt (170) abzutasten, und um einen maschinen-lesbaren Code, zum Lesen des ersten, eindeutigen Auftrag-Identifizierers, vorhanden auf dem ersten Auftrag-Referenz-Blatt (170), und zum Lesen des zweiten, eindeutigen Auftrag-Identifizierers, vorhanden auf dem zweiten, abgetasteten Auftrag-Referenz-Blatt (170), zu decodieren;
 eine Einrichtung zum Zugreifen auf den ersten Satz von elektronischen Seiten, gespeichert an der ersten Stelle, identifiziert durch den gelesenen, ersten, eindeutigen Auftrag-Identifizierer, und den zweiten Satz von elektronischen Seiten, gespeichert an der zweiten Stelle, identifiziert durch den gelesenen, zweiten, eindeutigen Auftrag-Identifizierer; und
 eine Einrichtung, die so angepasst ist, um, in Abhängigkeit, von einem Abtasten des ersten Auftrag-Referenz-Blatts (170) und des zweiten Auftrag-Referenz-Blatts (170), den ersten Satz von elektronischen Seiten mit dem zweiten Satz von elektronischen Seiten zusammenzustellen und um den zusammengestellten Satz an einer Speicherstelle zu speichern, um den zusammengestellten Auftrag zu bilden.

5. Elektronisches Drucksystem (2) nach Anspruch 4, das weiterhin aufweist:

eine Einrichtung zum Analysieren des abgetasteten Auftrag-Referenz-Blatts (170) und jedes abgetasteten Originals, um zu bestimmen, ob ein maschinen-lesbarer Code vorhanden ist.

40 Revendications

1. Procédé de formation d'un travail assemblé à partir d'un premier travail (156), représenté par un premier ensemble de pages électroniques et un deuxième travail (156), représenté par un deuxième ensemble de pages électroniques, dans un système d'impression électronique (2) comportant une imprimante (8) et un dispositif à balayage (6) adapté pour convertir les travaux (156) en ensembles de pages électroniques et pour décoder le code utilisable par un ordinateur, comprenant les étapes consistant à :

balayer lesdits premier et deuxième travaux pour générer lesdits premier et deuxième ensembles de pages électroniques à une première position dans une partie mémoire (61) ; attribuer un premier identificateur unique de travail

- (156) au premier travail mémorisé (156) pour indiquer la première position du premier travail mémorisé (156) dans la partie mémoire (61) ; à la demande, imprimer automatiquement une feuille de référence de premier travail (170) comprenant le premier identificateur unique de travail (170) en code utilisable par un ordinateur ; mémoriser le deuxième ensemble de pages électroniques à une deuxième position dans la partie mémoire (61) ; attribuer un deuxième identificateur unique de travail au deuxième travail mémorisé (156) pour indiquer la deuxième position du deuxième travail mémorisé (156) dans la partie mémoire ; à la demande, imprimer automatiquement une feuille de référence de deuxième travail (170) comprenant le deuxième identificateur unique de travail en code utilisable par un ordinateur ; lors du balayage de la feuille de référence du premier travail (170) :
- lire le premier identificateur unique de travail compris sur la feuille de référence de premier travail (170), et accéder au premier ensemble de pages électroniques mémorisées à la première position dans la partie mémoire (61) identifiée par le premier identificateur unique de travail lu (170) ; lors du balayage de la feuille de référence de deuxième travail (170) :
- lire le deuxième identificateur unique de travail compris sur la feuille de référence de deuxième travail (170), et accéder au premier ensemble de pages électroniques mémorisées à la deuxième position dans la partie mémoire (61) identifiée par le deuxième identificateur unique de travail lu ; en réponse au balayage de la feuille de référence de premier travail (170) et de la feuille de référence de deuxième travail (170) :
- compiler le premier ensemble de pages électroniques avec le deuxième ensemble de pages électroniques et mémoriser ledit ensemble compilé à une position de mémoire pour former le travail assemblé.
2. Procédé selon la revendication 1 comprenant en outre l'étape consistant à :
- imprimer le travail assemblé avec l'imprimante (8).
3. Procédé selon la revendication 1 ou 2, dans lequel

les étapes de balayages comprennent en outre l'étape consistant à :

- analyser une feuille de référence de travail balayée (170) et chaque original balayé pour déterminer si du code utilisable par un ordinateur est présent.
4. Système d'impression électronique (2) destiné à former un travail assemblé à partir d'un premier travail (156), représenté par un premier ensemble de pages électroniques, et un deuxième travail (156), représenté par un deuxième ensemble de pages électroniques, comprenant :
- un dispositif de balayage (6) étant adapté pour convertir le premier travail (156) en premier ensemble de pages électroniques et le deuxième travail (156) en deuxième ensemble de pages électroniques ;
- un moyen (61) destiné à mémoriser le premier ensemble de pages électroniques à une première position et le deuxième ensemble de pages électroniques à une deuxième position ;
- un moyen étant adapté pour attribuer un premier identificateur unique de travail au premier travail mémorisé (156) pour indiquer la première position du premier travail mémorisé (156) et un deuxième identificateur unique de travail au deuxième travail mémorisé (156) pour indiquer la deuxième position du deuxième travail mémorisé (156) ;
- une imprimante (8) étant adaptée pour imprimer à la demande automatiquement une feuille de référence de premier travail (170) comprenant le premier identificateur unique de travail en code utilisable par un ordinateur et une feuille de référence de deuxième travail (170) comprenant le deuxième identificateur unique de travail en code utilisable par un ordinateur ;
- le dispositif à balayage (6) étant en outre adapté pour balayer la feuille de référence de premier travail (170) et la feuille de référence de deuxième travail (170) et pour décoder du code utilisable par un ordinateur, pour lire le premier identificateur unique de travail compris sur la feuille de référence de premier travail (170) et lire le deuxième identificateur unique de travail compris sur la feuille de référence de deuxième travail balayée (170) ;
- un moyen destiné à accéder au premier ensemble de pages électroniques mémorisées à la première position identifiée par le premier identificateur unique de travail lu et au deuxième ensemble de pages électroniques mémorisées à la deuxième position identifiée par le deuxième identificateur unique de travail lu ;
- un moyen adapté pour compiler, en réponse au

balayage de la feuille de référence de premier travail (170) et de la feuille de référence de deuxième travail (170), le premier ensemble de pages électroniques avec le deuxième ensemble de pages électroniques et pour mémoriser ledit ensemble compilé à une position de mémoire pour former le travail assemblé. 5

5. Système d'impression électronique (2) selon la revendication 4, comprenant en outre : 10

un moyen destiné à analyser la feuille de référence de travail balayée (170) et chaque original balayé pour déterminer si du code utilisable par un ordinateur est présent. 15

20

25

30


35

40

45

50

55






FIG. 2

FIG. 3




FIG. 4








FIG. 5



JOB PROGRAM   

JOB: Standard 1 DEFAULT 152 **JOB Scorecard**

JOB: Standard 1 DEFAULT 153 **Job Types & Tickets**

PAGE LEVEL **COVERS** **Close**

Job Ticket for: 1 **Account: DEFAULT** **Page Level: Off**

Job Type: Standard	Page Level: Basic	Page Level: Special
Job Level	Document Description:	Crop:
Job Identification:	8.5 x 11.0 Standard	Off
Destination:	Paper Stock:	Window:
Print & Delete	8.5 x 11.0 Standard White	Off
Quantity:	Reduce / Enlarge:	Image Shift:
1	100%	Off
Output:	Sides Imaged:	Merge:
Stacker Collated	1 → 1	Off
Page Numbering:	Image Quality:	Rotate:
Off	Standard Sharpness On	Off

Restore Defaults **Interrupt** **Printer Options** **Stop Scan** **Stop Print** **Job Supplement** **Start Scan**

62 **67**

FIG. 6




FIG. 7

FIG. 8




FIG. 9A





FIG. 9B







FIG. 10

FIG. 11






FIG. 12